Washdown Duty OSHA Circulation Fans

Increase safety and productivity in work areas where strict hygiene requirements exist with stainless and washdown duty air circulators from Schaefer. These single speed, direct drive fans have stainless steel guards, stainless steel or polypropylene blades and a choice of all stainless steel (for highly corrosive environments) or epoxy-coated washdown duty motors. They are ideally suited for kitchens, hospitals, food and beverage processing facilities, and other clean, corrosive or humid environments. Built tough to withstand a long lifetime of use and pressure washing.

- Two washdown duty motor types available:
  EWD (1) USDA® approved non-toxic white epoxy coated washdown duty. 1-year warranty.
  SWD (2) All stainless corrosive environment washdown duty. 2-year warranty.
- All models come standard with electro-polished 304 stainless steel, OSHA spaced guards.
- Choice of stainless steel or polypropylene blades.
- Maximum airflow and fan life due to careful matching of motors and engineered fan blades.
- Totally enclosed air over or totally enclosed fan cooled, maintenance free, heavy-duty ball bearing, permanent split capacitor, internally thermally protected motors for pressure washing and long life.
- Durable, stainless steel wall and ceiling mounting options available.

Model	Description	HP	Volts	Amps	CCFM	RPM
12CFO-EWDP	12" fan, epoxy motor/poly blades	1/3	115/230	4.9/2.5	1680	1700
12CFO-EWDP-3	12" fan, epoxy motor/poly blades	1/3 - 3-Phase	208-230/460	1.9-1.8/0.9	1747	1725
16CFO-EWDP	16" fan, epoxy motor/poly blades	1/3	115/230	4.9/2.5	3409	1700
16CFO-EWDP-3	16" fan, epoxy motor/poly blades	1/3 - 3-Phase	208-230/460	1.9-1.8/0.9	3508	1725
20CFO-EWDP	20" fan, epoxy motor/poly blades	1/3	115/230	4.9/2.5	4922	1700
20CFO-EWDP-3	20" fan, epoxy motor/poly blades	1/3 - 3-Phase	208-230/460	1.9-1.8/0.9	5036	1725
24CFO-EWDS	24" fan, epoxy motor/stainless steel blades	1/2	115/230	5.9/2.9	7789	1700
24CFO-EWDS-3	24" fan, epoxy motor/stainless steel blades	1/2- 3-Phase	208-230/460	2.5-2.0/1.0	7700	1725
24CFO-EWDP	24" fan, epoxy motor/poly blades	1/2	115/230	5.9/2.9	7346	1700
24CFO-EWDP-3	24" fan, epoxy motor/poly blades	1/2- 3-Phase	208-230/460	2.5-2.0/1.0	7451	1725
24CFO-SWDP	24" fan, stainless steel motor/poly blades	1/2	115/230	8.2/4.1	7307	1725
24CFO-SWDP-3	24" fan, stainless steel motor/poly blades	1/2- 3-Phase	208-230/460	1.5-1.6/0.8	7446	1740
24CFO-SWDS	24" fan, stainless steel motor/s.s. blades	1/2	115/230	8.2/4.1	6855	1725
24CFO-SWDS-3	24" fan, stainless steel motor/s.s. blades	1/2- 3-Phase	208-230/460	1.5-1.6/0.8	6913	1740
30CFO-EWDS	30" fan, epoxy motor/stainless steel blades	1/2	115/230	5.9/2.9	10,000	1700
30CFO-EWDS-3	30" fan, epoxy motor/stainless steel blades	1/2- 3-Phase	208-230/460	2.5-2.0/1.0	10,000	1725
30CFO-SWDS	30" fan, stainless steel motor/s.s. blades	1/2	115/230	8.2/4.1	10,000	1725
30CFO-SWDS-3	30" fan, stainless steel motor/s.s. blades	1/2- 3-Phase	208-230/460	1.5-1.6/0.8	10,000	1740

SCHAEFER

800-779-3267 • Fax: 320-251-2922
sales@schaeferfan.com • www.schaeferfan.com

©2010 Schaefer Ventilation Equipment 6-10